

Name: 8IGHT-T 2.0 Race Roller Vehicle Setup		Date: _____		Event: _____	
City: _____		State: _____		Track: _____	
Track <input type="checkbox"/> Indoor <input type="checkbox"/> Tight <input type="checkbox"/> Smooth <input type="checkbox"/> Hard Packed <input type="checkbox"/> Blue Groove <input type="checkbox"/> Wet <input type="checkbox"/> Low Bite <input type="checkbox"/> High Bite Conditions <input type="checkbox"/> Outdoor <input type="checkbox"/> Open <input type="checkbox"/> Rough <input type="checkbox"/> Loose/Loamy <input type="checkbox"/> Dry <input type="checkbox"/> Dusty <input type="checkbox"/> Med Bite <input type="checkbox"/> Other _____					

Front Suspension

Toe: 2 degrees of toe-out
 Ride Height: 39mm
 Camber: -1 degree
 Caster: Stock
 Sway Bar: 2.3mm
 Piston/Oil: 55/35wt
 Spring: Black 5.0lbs
 Limiter/Droop: _____
 Overall Shock Length: _____
 Steering Ackerman: Long
 Bump Steer: Down
 Camber Link: 2/A
 Shock Location: 2/Middle
 Receiver Battery Type: Losi LiPo

Differentials

Front: ☒ Standard ☐ Smart
 Spring Wire Dia: _____
 Qty of Springs: _____
 Ramp Plate: _____
 Grease: _____
 Diff Fluid: 7000wt Losi
 Center: ☒ Standard ☐ Smart
 Spring Wire Dia: _____
 Qty of Springs: _____
 Ramp Plate: _____
 Grease: _____
 Diff Fluid: 10000 wt Losi

Ackerman

Bump Steer

Notes: _____

Rear Suspension

Toe: 3.5 degrees
 Anti-Squat: 3 degrees
 Ride Height: 42mm
 Camber: -2 degrees
 Rear Hub Spacing: 1 spacer foward
 Sway Bar: 2.3mm
 Piston/Oil: 56/30wt
 Spring: Grey 4.0lbs
 Limiter/Droop: _____
 Overall Shock Length: _____
 Camber Link: 1/B
 Shock Location: 3/Middle
 Rear Diff Fluid: 2000wt Losi

Notes: _____

Engine

Engine: _____ Fuel: Nitrotane 30%
 Glow Plug: _____ Head Clearance: _____
 Pipe/Header: _____ Gearing: 13/50

Clutch

Clutch Shoes and Springs Info
4 Aluminum Shoes
2 Gold and 2 Green Springs
Aluminum Flywheel

Tires

	Type	Compound	Insert
Front:	<u>XTT</u>	<u>Blue</u>	_____
Rear:	<u>XTT</u>	<u>Blue</u>	_____
Notes:	_____		
