

Name: <u>Adam Drake</u>		Date: _____	Event: <u>Nova Rossi GP</u>
City: <u>North Benflee, England</u>		State: _____	
Track Conditions: <input type="checkbox"/> Indoor <input checked="" type="checkbox"/> Tight <input checked="" type="checkbox"/> Smooth <input checked="" type="checkbox"/> Hard Packed <input checked="" type="checkbox"/> Blue Groove <input type="checkbox"/> Wet <input type="checkbox"/> Low Bite <input type="checkbox"/> High Bite		Astro	
<input checked="" type="checkbox"/> Outdoor <input type="checkbox"/> Open <input type="checkbox"/> Rough <input type="checkbox"/> Loose/Loamy <input checked="" type="checkbox"/> Dry <input type="checkbox"/> Dusty <input checked="" type="checkbox"/> Med Bite <input type="checkbox"/> Other _____			

Front Suspension

Toe: 3 Degree Toe Out
 Ride Height: 28mm
 Camber: -1 Degrees
 Caster: Stock
 Sway Bar: 2.7mm
 Piston/Oil: 54 (drilled)/40wt Losi
 Spring: Silver
 Limiter/Droop: _____
 Overall Shock Length: 94.8mm
 Steering Ackerman: Long
 Bump Steer: Down
 Camber Link: 2/A
 Shock Location: 2/Inside
 Receiver Battery Type: Losi

Differentials

Front: ☒ Standard ☐ Smart
 Spring Wire Dia: n/a
 Qty of Springs: n/a
 Ramp Plate: n/a
 Grease: n/a
 Diff Fluid: 7000wt
 Center: ☒ Standard ☐ Smart
 Spring Wire Dia: n/a
 Qty of Springs: n/a
 Ramp Plate: n/a
 Grease: n/a
 Diff Fluid: 7000wt

Ackerman

Long

Short

Bump Steer

Up Down

Notes: Adjustable pivots with 0 inserts.
55 piston with all six holes drilled out with a #54 bit.
1/4 rebound.

Rear Suspension

Toe: 2 Degrees
 Anti-Squat: 3 Degrees
 Ride Height: 28mm
 Camber: -2 Degree
 Rear Hub Spacing: Hubs all the way forward.
 Sway Bar: 2.7mm
 Piston/Oil: 56/25wt Losi
 Spring: Green
 Limiter/Droop: _____
 Overall Shock Length: 107mm
 Camber Link: 2/B
 Shock Location: 2/Inside
 Rear Diff Fluid: 3000wt

Notes: Adjustable pivots with 1's up in the front and 1's in. Alum. rear hubs.
1/4 rebound.

Engine

Engine: Nova Rossi Plus 4 Fuel: Nitrotane 30%
 Glow Plug: Nova Rossi 6 (C6TGC) Head Clearance: _____
 Pipe/Header: 9901 / 41021 Gearing: 13/48

Clutch

Clutch Shoes and Springs Info

2 Aluminum with Green Springs
2 Plastic with Black Springs
Steel Flywheel

Tires

Type	Compound	Insert
Front: _____	_____	_____
Rear: _____	_____	_____
Notes: _____		