

SETUP SHEET



						<i>_</i>	7	
Name: Adam Drake		Date: 2	Date: 2009			Event: Standard set-up		
City: Sta	ite:	Track:						
	Hard Packed □ Blue Groov .oose/Loamy □ Dry	e □ Wet □ Dusty	☐ Low Bite☐ Med Bite	☐ High Bite☐ Other	•			
Front Suspension	Differentials		Ackerr	man	Bump S	Steer		
Toe: 2 degrees of toe-out	Front: 🛮 Standard 🗖 Smart	:	Long		Up D			
Ride Height: 39mm	Spring Wire Dia:		Shor		ор В	OWIT		
Camber: -1 degree	Qty of Springs:			ÆJ				
Caster: Stock	Ramp Plate:					3-		
2.2	Grease:					ž- 1-		
	Diff Fluid: 7000wt Losi				_	Outside		
Spring: Black 3.4lbs	Diff Flata.			ВА		-Middle -Inside	3	
110mm	Center: Standard Sm	art				Inside		
	Spring Wire Dia: ——				1000		00	
Long	Qty of Springs:——						70	
Davin	Ramp Plate:				1			
2/4	Grease:		V 4:		مادانی مدم	مال ۵: موسط		
2 / 1 / 1 / 1 / 1	Diff Fluid: 10000 wt Lo	osi	Notes: Adju	ustable piv	OLS WILLI	an o mseri	.5.	
Receiver Battery Type: Losi LiPo	J.II. Flata.							
Theodiver Battery Type:								
Rear Suspension								
Toe: 3 degrees								
Anti-Squat: 3 degrees		_						
Ride Height: 42mm		_						
Camber: -2 degrees						3		
Rear Hub Spacing: Middle			P	ÇВА		2 <u></u> 1		
Sway Bar: 2.3mm								
Piston/Oil: 56/32.5wt					1	side ddle	2 0	
Spring: Grey 4.0lbs					1.1	nside		
Limiter/Droop: 130mm		—						
Overall Shock Length:								
Camber Link: 1/B Shock Location: 3/Middle		_	4					
Rear Diff Fluid: 2000wt Losi		_						
Engine Engine		-	Notos: Adju	ıstable piv	ots with	1's up in	the front and	
Engine: GRP .21 Tuned	Fuel: Nitrotane 30%		0's in the re			· ·		
Glow Plug:	Head Clearance:							
600 00=0 / 1	Gearing: 13/50							
Clutch Shoes and S		Tires	Туре	_	Compo	und	Insert	
2 Aluminum Shoes v		Front:	XTT	BI	ue			
2 Plastic Shoes with (·	Rear:	XTT	Bl	lue			
Steel Flywheel		Notes: .						