



Setup Sheet

Driver: W. Lee

Date: _____

Track: _____

☐ Indoor
☐ Outdoor

☐ Smooth
☐ Rough

☐ Tight / ☐ Open

☐ Slippery
☐ High-Bite
☐ Blue-Groove

FRONT SUSPENSION (Circle or Check the Appropriate Settings)

Toe ☒ In 1°
☐ Out _____

Ride Height Arms level

Camber ☒ - 1°
☐ + _____

Caster ☒ Stock 30°
☐ Other _____

Sway Bar ☒ No
☐ Yes size: _____

of washers under steering / tie-rod ball studs

Spindle ball stud: 1

Bellcrank ball stud: 0


Spindle Location

☐ Top
☐ Middle
☒ Bottom

☐ A
☒ B
☐ C

☒ Long
☐ Short

☒ Long
☐ Short



☐ 4
☐ 3
☒ 2
☐ 1

of washers under ball stud
2

☐ Inside
☒ Middle
☐ Outside

☐ 1
☐ 2
☒ 3

Front Shocks

Oil: 30wt.

Piston: #56 ☒ Standard / ☐ Drilled

Spring: Red Internal: ☐ Yes / ☒ No

Limiters: ☒ Inside- "A" (0.120") ☐ Outside- _____

REAR SUSPENSION

Body: MF2

Toe-In ☒ Inside 3°
☐ Outside _____

Spoiler: Standard

Pivot Support ☐ No Shim
☒ Shim Under Front— # of shims: 2

1 Shim = 1°

Ride Height Dogbones just below level

Camber ☐ - 0°
☐ + _____

Drive Shafts ☒ Dogbones ☐ Aluminum
☐ CVDs ☒ Steel

Rear Hub Spacing ☐ Forward
☒ Center
☐ Rear

Sway Bar ☒ No
☐ Yes size: _____

Rear Shocks

Oil: 30wt.

Piston: #56 ☒ Standard / ☐ Drilled

Spring: Red Internal: ☐ Yes / ☒ No

Limiters: ☐ Inside- _____ ☐ Outside- _____

☐ 4
☒ 3
☐ 2
☐ 1

☒ 1
☐ 2
☐ 3

☐ Short
☒ Long

☐ Outside
☒ Middle
☐ Inside

☐ Outside
☐ Inside

☒ Long
☐ Short

Tires

Front: 8-Rib (LOSA7507R)

Compound
Red

Foam
Standard

Rear: King Pin (LOSA7637R)

Red

Standard

Motor: _____ Pinion/Spur: _____ / 86

Battery Position: Middle

Weather Conditions/Notes: _____